SumpFlushGrandTwin

The SumpFlushGrandTwin is a fully automatic waste water pumping system suitable for pumping surface and/or ground water to a higher level when gravity drainage is not possible and/or economical to install.

The SumpFlushGrandTwin offers a larger chamber than the standard SumpFlush. The system can accept waste from car parks, car washes, floor areas, down pipes, cavity membrane systems or similar.

The systems comprise of a polyethylene chamber, $1\frac{1}{4}$ " PVC internal pipework, two powerful 240V submersible pumps, 110mm inlets, 50mm cable duct, and $1\frac{1}{4}$ " discharge. The systems are very versatile, enabling the installer to locate inlets to their specifications.

The systems come with a locking, pedestrian duty, access cover.

It is recommended that a high level alarm product is installed, which alerts the end user if the water rises above the normal operating level within the chamber. High level alarm kits can be purchased to installer specifications.


A battery backup system is also highly recommended especially where inflow cannot be controlled, for example in groundwater and surface water applications. Battery backup systems can be purchased to installer specifications.

KEY FEATURES

- Larger chamber for increased surface areas.
- Reliable 'OpenFlow'
 wastewater pumps.
- Supplied with a solid access cover as standard. Other access cover types are available.
- A range of battery backup options are available.
- A range of high level alarms and telemetric monitoring systems are available.



PUMP CURVE



DIMENSIONS	(mm)
DIMENSION	(,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,

•	· ·		
Product	Diameter	Height	
SumpFlushGrandTwin	900	1250	
Product	Length	Height	Depth
Clear opening	600	450	-
(including frame)	640	490	23mm

Weiaht

WEIGHT (kg)

Product	We
SumnFlushGrandTwin	95

SumpFlushGrandTwin	

SUITABLE FOR WASTE TYPE Above ground Above Above Retro-fit WASTE TYPE Grey Ground Surface Storm Surface



TECHNICAL DATA

Chamber	
Colour	White
Material	Polyethylene
Max capacity *	330 litres
Lifting eyes	Yes
Discharge size	1¼"

* Actual capacity will depend on the invert height of lowest inlet.

Pump	
Power supply	230 V AC
Rated current	1.9 A per pump
Motor rating	180 W per pump
Frequency	50 Hz
Revolutions per min.	2800 rpm per pump
Max vertical output	6.7 m
Max flow rate	2.9 l/s
Max liquid temp.	<50°C
Discharge size	1¼" / 32 mm
Free passage	10 mm
Cable length	5 m
Colour	Red

Access cover	
Cover material	Galvanised steel
Frame material	Polypropylene
Туре	Solid top
Loading	Facta A
Locking	Yes



All our products can be customised to your requirements.

For more information please call our sales team on 01442 211554.

DELIVERING PUMPED AND DRAINAGE SOLUTIONS FOR OVER 25 YEARS



We provide pumped and drainage products and services to the public and private sectors, including residential, commercial, hospitality and retail.

We are proud of the long-term relationships we have built with our clients and partners, delivering cost effective, robust and dependable products and services.

PROJECT SERVICES

- Project design
- Site surveys
- Installations
- Refurbishments

AFTERSALES SERVICES

- Planned servicing
- Emergency call outs
- Commissioning
- Monitoring

DRAINAGE SERVICES

- Tankering
- Jetting
 - Drainage CO
- Surveys
- Cleaning and de-scaling
 - Structural repairs
- Drainage CCTV
 Excavations
 - Root cutting

12-MONTH GUARANTEE

Your products are protected by a 12-month guarantee. Please refer to our Terms and Conditions at <u>www.edincare.com</u>

HOW TO ORDER

Order online at <u>www.edincare.com</u> Call Sales on 01442 211554 Email <u>sales@edincare.com</u>

www.edincare.com

- Discover our products and services
- Order products online
- Case studies and articles
- · Brochures and technical documents

Protect your property with an Edincare Service Agreement

As with all pumped and drainage systems, regular maintenance is essential to ensure optimum performance and minimal downtime. Our Service Agreements comprises planned preventive maintenance visits at an agreed frequency, we also service other manufacturers' equipment regardless of type, make and age.

- ✓ Validates your building insurance
- Reduces the risk of failure
- Increases the life expectancy of your equipment
- Priority callouts and 24/7 out-of-hours service
- Reduced rates for emergency call outs
- Flexible payment options (Direct Debit)



+44 (0)1442 211554 info@edincare.com www.edincare.com

Unit 8, Heron Business Park, Eastman Way, Hemel Hempstead, Hertfordshire, HP2 7FW

Part of the Edincare Group of Companies www.edincaregroup.com

Our policy is one of continuous product improvement, we reserve the right to change specifications and prices without prior notice. All information is given in good faith. No responsibility can be accepted for errors, omissions or incorrect assumptions. © Omni Pump International Ltd Va Edincare Pumps & Edincare Drains. All rights reserved.