ACCESSORIES

Ama-Porter 601NE



The state of the art Ama-Porter 601NE is designed for high operating reliability and is designed to give top performance due to a generously sized motor, thermal overload protection. The pump comes in a manual, automatic, single and three phase versions.

The submersible pump with a 60mm solids clearance offers reliable and effective dewatering. The compact shape and small sump requirements ensure a quick and cost effective installation of the pump. Can be supplied free standing, or pedestal mounted for permanent installations.

APPLICATION

- Factories and warehouses
- Housing developments
- Commercial buildings
- Retail and leisure
- Domestic properties

• Ground water

IMPELLOR TYPE

- Vortex
- Surface water
- Storm water

Grey water

Foul water

KEY FEATURES

- Trouble-free operation; clogging is prevented by a free flow impeller
- Easy installation and removal with an automatic bolt-free connection
- Internal overload protection
- Long service life due to a shaft made of corrosion-resistant stainless steel and a bi-rotational mechanical seal

PUMP CURVE



DIMENSIONS

AmaPorter 601NE	
Height	408mm inc. feet
Width	224mm
Length	374mm inc. outlet

TECHNICAL SPECIFICATIONS

AmaPorter 601NE	Single Phase
Power Supply	240V AC
Rated Current	6A
Motor Rating	750W
Frequency	50Hz
Revolutions Per Minute	2900rpm
Max. Vertical Output	8.2m
Max. Flow Rate	8.2 l/s
Max. Liquid Temperature	<40°C
Discharge Size	DN65
Free Passage	60mm
Cable Length	10m
Weight	26kg
Colour	Blue
Impellor Type	Vortex
Control	Manual



+44 (0)1442 211554 info@edincare.com www.edincare.com

Unit 8, Heron Business Park, Eastman Way, Hemel Hempstead, Hertfordshire, HP2 7FW

Our policy is one of continuous product improvement, we reserve the right to change specifications and prices without prior notice. All information is given in good faith. No responsibility can be accepted for errors, omissions or incorrect assumptions. © Copyright 2023 Omni Pump International Ltd t/a Edincare Pumps & Edincare Drains. All rights reserved.