

# SumpFlush Twin 650-1000 c/w Timer Control Panel



#### **SYSTEM OVERVIEW**







10-hour changeover control panel with high level alarm and volt-free contact



11/4" Class E PVC pipework



11/4" Class E PVC discharge



110 mm inlet



50 mm cable duct



50 mm vent duct



Access cover, solid top, locking, galvanised steel, FACTA A

The SumpFlush Twin 650-100 is a fully automatic wastewater pumping system suitable for pumping surface and/or ground water to a higher level when gravity drainage is not possible and/or economical to install.

The system provides up to 165 litre storage capacity depending inlet depth. It can accept waste from car parks, car washes, floor areas, down pipes, cavity membrane systems or similar.

It is not suitable for receiving foul waste. Contact our Sales Team for advice on a suitable foul water packaged pumping stations for your property.

The system consists of a polyethylene tank, two automatic wastewater submersible pumps, timer control panel and a solid top, locking, galvanised steel access cover (FACTA A).

The control panel balances the wear between the two pumps, and provides a high level alarm and volt-free contacts for remote monitoring.

It discharges to solvent welded  $1\frac{1}{4}$ " Class E PVC. Optional discharge reducer kits can increase external discharge diameter to  $1\frac{1}{2}$ " or 2" to reduce friction loss.

It is easy to install as inlets can be positioned to your site's requirements. Inlet information to be supplied at time of order, or can be drilled on site.

#### **KEY FEATURES**

- · Vortex impellor for high flow rates
- Control panel for timed changeover, high level alarm and volt-free contacts
- Up to 165 litres storage capacity
- Compact chamber for limited space installations
- Ideal for an extension, outbuilding, basement or similar
- 450 mm x 450 mm clear opening
- · Variable inlet positions to suit site
- A range of battery backup systems are available
- Quick and simple to install

# **WASTE TYPE**









1

urface

For groundwater and surface water applications where inflow cannot be controlled, a battery backup system should be used, in accordance with BS 8102:2022 and PCA Guidelines. Battery backup systems can be purchased to your specification.

#### **RECOMMENDED ACCESSORIES**














All our products can be customised to your requirements. For more information and advice please call our Sales Team on 01442 211554.




# SumpFlush Twin 650-1000 c/w Timer Control Panel

#### **TYPICAL INSTALLATION**




#### **PUMP SPECIFICATIONS**

Number of pumps	Two
Impellor type	Vortex
Control	Automatic
Power supply	230 VAC
Rated current per pump	1.9 A
Motor rating (P2) per pump	180 W
Revolutions per min.	2800
Discharge size	11⁄4"
Free passage	10 mm
Max. vertical output per pump	6.8 m
Max. flow rate per pump	2.9 l/s
Max liquid temp.	<40 °C
Cable length	5 m
Weight	5.2 kg



# **CHAMBER DIMENSIONS**

Shows indicative capacities from lowest inlet invert.



#### Permitted connection positions

Discharge only Inlet location allowed	Cable ducts and vents only	No drilling allowed
---------------------------------------	----------------------------	---------------------

# **CHAMBER SPECIFICATIONS**

Internal pipework	11/4" OD Class E PVC
Discharge pipework	11/4" OD Class E PVC
Lifting eyes	No
Maximum storage capacity	165 litres
Chamber material	Tank-grade polyethylene
Dimensions (Ø x H)	750 x 1000 mm
Clear opening	450 x 450 mm

# **ACCESS COVER**

Material	Galvanised steel
Cover type	Solid top
Locking	4 screws
Loading	Pedestrian duty FACTA A
Clear opening (H x W)	450 x 450 mm
Dimensions (H x W x D)	515 x 515 x 40 mm



#### **DELIVERING PUMPED AND DRAINAGE SOLUTIONS FOR OVER 30 YEARS**

**Packaged pumping stations** 

**Waste water pumping systems** 

**Macerators and macerating toilets** 

Floor mounted pumping stations

Fat, oil and grease separating systems

**Rainwater harvesting systems** 

**Battery backup systems** 

Adoptable pumping stations

Submersible pumps

**Accessories** 



We provide pumped and drainage products and services to the public and private sectors, including residential, commercial, hospitality and retail.

We are proud of the long-term relationships we have built with our clients and partners, delivering cost effective, robust and dependable products and services.

#### **PROJECT SERVICES**

- Project design
- Site surveys
- Installations
- Refurbishments

# **AFTERSALES SERVICES**

- Planned servicing
- · Emergency call outs
- Commissioning
- Monitoring

# **DRAINAGE SERVICES**

- Tankering
- Cleaning and de-scaling
- Jetting
- Structural repairs
- Drainage CCTVExcavations
- Surveys
- · Root cutting

# **12-MONTH GUARANTEE**

Your products are protected by a 12-month guarantee. Please refer to our Terms and Conditions at www.edincare.com

#### **HOW TO ORDER**

Order online at www.edincare.com Call Sales on 01442 211554 Email sales@edincare.com

# www.edincare.com

- Discover our products and services
- Order products online
- Case studies and articles
- · Brochures and technical documents

# **Protect your property with an Edincare Service Agreement**

As with all pumped and drainage systems, regular maintenance is essential to ensure optimum performance and minimal downtime. Our Service Agreements comprises planned preventive maintenance visits at an agreed frequency, we also service other manufacturers' equipment regardless of type, make and age.

- ✓ Validates your building insurance
- Reduces the risk of failure
- ✓ Increases the life expectancy of your equipment
- ✓ Priority callouts and 24/7 out-of-hours service
- Reduced rates for emergency call outs
- Flexible payment options (Direct Debit)





+44 (0)1442 211554 info@edincare.com

www.edincare.com **In** edincarepumps Unit 8, Heron Business Park, Eastman Way, Hemel Hempstead, Hertfordshire, HP2 7FW

Part of the Edincare Group of Companies www.edincaregroup.com

















